

DATASHEET




HIMAG[™] SURFACE WAVE ABSORBER

PART#: AB340-0068 THICKNESS: .020" 14-18 GHz

Modus Advanced, Inc. Surface Wave Absorber is a thin, very highly loaded material, having high loss at microwave frequencies, while maintaining the desirable characteristics of elastomeric binders. Surface Wave Absorbers are the most heavily magnetically loaded absorber, designed to exhibit the highest loss, and intended to be applied to metal surfaces for traveling or surface wave attenuation.

The standard elastomer for this product series is silicone. Other elastomer formulations are available which may be better suited for specific environmental conditions.



CUSTOMERS ALSO SEARCHED:

RF Absorbing Material Radio Frequency Absorbing Material **RF** Absorbing Foam RF Absorber Radar Absorbing Material Absorber Foam **RF** Absorber Material Microwave Absorber Material

RF Absorbers Radio Frequency Absorption Microwave Absorbing Materials Absorbing Material **RF** Materials Microwave Absorbing Material

Microwave Absorber Radar Absorber

Radar Absorbant Material Absorbing Foam EMI Absorbing Material Wave Attenuation Devices Magnetic Foam Sheets Radar Absorbing Materials **RF** Attenuation Radar Absorbing Material

ELECTRICAL PERFORMANCE: The performance plot sho

reflection loss performance of this material. Reflection loss is measured on a NRL arch.

For more information on the

technical

NRL arch test set-up, pleas contact a Modus™ technica

representative. Additional electrical test data may be

available upon request

on the left, illustrates the



APPLICATIONS

- Traveling or Creeping surface wave absorption
- Resonant Cavity Attenuation
- EM Reduction
- Mounted to an IC on a PCB
- Mounted directly on a micro-strip
- High Frequency Interference
- Inside a shielding can

FEATURES AND BENEFITS

- Tough material can survive outdoor exposure
- Very thin for compact locations
- Flexible elastomeric material will not crack
- Support broad frequency range
- RoHS Compliant
- Halogen Free

TYPICAL PROPERTIES

- Sheet Size: 24" x 24"
- Color: Dark Grey
- Elastomer: Silicone
- Operating Temperature: -60°F to 375°F
- Flame Rating: UL94-V0
- Hardness: Shore A 60-80

AVAILABILITY

Without adhesive - Part # AB340-0068

With adhesive - Part # AB340-0068-AD

Sheets, Die Cut, Kiss Cut Pads

MODUS ADVANCED TAKES YOU FROM IDEA TO IGNITION







3. SOLUTION We strategically





We are Modus! With multiple locations in North America and China, Modus Advanced, Inc. is a diversified custom manufacturer which converts EMI Shielding, Environmental Gasket Materials, Microwave Absorbers, Acoustic Materials, Thermal Interface Materials and other high performance materials into finished parts. Modus utilizes its 40 years as an established provider of high quality, reliable products to create precisely what customers specify. Innovative processes; custom fabrication utilizing performance materials; an on time delivery record of more than 99% means Modus is well positioned to help your company succeed.

This information is based on data believed to be reliable, but Modus makes no warranties, expressed or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties, but should not be used to establish specification limits or used alone as the basis of design. Modus' liability to purchasers is expressly limited to the terms and conditions of sales listed on our website

ABOUT MODUS